



PRETEK

APPROVAL SHEET

CUSTOMER NAME :

ITME : D 型混装大电流连接器

MODEL : DMP0-13W3S-03

MATERIEL NO :

DATE : 08/06/2007

APPROVED BY:

深圳市普瑞泰电子有限公司

地址: 深圳市福田区深南中路南光捷佳大厦2121室

电话: 0755-83981317 83983895

传真: 0755-83981375

网址: www.szpretek.com

邮箱: liubinwu@szpretek.com, wj@szpretek.com

一.	Material NO 物料代码:
二.	Material Name 物料名称: D 型混装 (10+3) 芯短焊线插头 (孔)
三.	Product Type 产品型号: DMP0-13W3S-03
四. Technical features 技术参数:  1. Electric characteristic 电气特性 1.1 Rated current 额定电流: For heavy current contact 大电流接触件 30A For Signal contact 信号接触件 5A 1.2 Rated voltage 额定电压: 250V 1.3 Insulation resistance 绝缘电阻: $\geq 1000M \Omega$ 1.4 Voltage proof 耐电压: 1000V AC 1.5 Contact resistance 接触电阻: For heavy current contact 大电流接触件 $\leq 5 m \Omega$ For Signal contact 信号接触件 $\leq 10 m \Omega$ 2. Mechanical characteristic 机械特性 Mating Force 插入力: For heavy current contact 大电流接触件 $\leq 5.0N$ For Signal contact 信号接触件 $\leq 2.0N$ Unmating Force 分离力: For heavy current contact 大电流接触件 $\geq 1.0N$ For Signal contact 信号接触件 $\geq 0.6N$ Mechanical Durability 机械寿命: 500cycles 500 次 3. Material and surface plating 材料及表面处理 3.1 Contact 接触件 Material 材料: phosphorous bronze 青铜 production Technique 生产工艺: For heavy current contact 大电流接触件 Turing 车削加工 For Signal contact 信号接触件 Punching 冲压加工 Surface plating 表面处理: Contact area Plating 5u", Gold over Nikel, other area Plating Sn voer Nikel 接触区域镀金 5u", 其余镀纯锡 3.2 Housing 基座 Material 材料: PBT, With GF, UL 94V-0 Black production Technique 生产工艺: Injecting 注塑加工 3.3 Sheel 外壳 Material 材料: Steel Strip 钢带 production Technique 生产工艺: Punching 冲压加工 Surface plating 表面处理: Plating Ni 镀镍 4. Environment 工作环境 Temperature range 工作温度: $-55^{\circ}C \sim 105^{\circ}C$ Ralative humidity 相对湿度: $40^{\circ}C$ 时, (90-95) % Vibration 振动: 10Hz~2000Hz, Acceleration 加速度 $196m/s^2$	

Shock 冲击:	Acceleration490 m/s ²
五. Most figure size 最大外型尺寸:	53×12.5×15.6
六. Material introduction 物料简介: 1. Basic instance 基本情况 The design of electrical features and Mechanical features is based on IEC60807-2. 电性能和机械性能依据 IEC60807-2、IEC60603-2 标准进行设计。 The connector is socket of Series D Rectangular Connector。Its terminal method is wire jointing, it could be applied with DMP-13W3P. 该连接器为 D 系列矩形混装插头，端接方式为导线焊接，可与 DMP-13W3P 配合使用。 2. Pack and Storage 包装储存 Products are Packed with plastic box. The packing list must be in the packing box which has been gave clear indication of designation、type、lot number and products total number. The products with packing are saved up at storeroom which environment temperature is 5℃～30℃, humidity≤80%, no acidity、no alkalescence and other corrosive gas, under these conditions the stockpile period doesn't exceed tow years from production date. 产品采用吸塑盒包装，箱内应有装箱单，装箱单及包装箱上注明产品名称、型号、批号及产品总数量。 包装好的产品应放环境温度为 5℃～30℃，相对湿度在 80%以下，周围空气中无酸性、碱性或其他腐蚀性气体的库房里储存，在上述条件下，储存期自生产日期不超过两年。 3. In point criterion 适用标准: IEC60807-2 4. Technique use 工艺使用: Wire jointing 导线焊接	